

**341003 (D01H5)**

Drop-in bain-marie, with one well (5 GN container capacity)

Main Features

- Electronic overheating protection.
- CB and CE certified by a third party notified body.
- Designed to be positioned in flush installation providing improved cleanability and suitable for modern design installations.
- Available drop-in dimensions: 2, 3, 4, 5, 6 GN.
- Designed to serve the food in gastronorm containers.
- Suitable for GN 1/1 containers with a maximum height of 200 mm.
- Automatic water refill guarantees constant heating performances and prevent unit breakage.
- Precise temperature control and setting at 0,1°C .
- As standard the product comes with digitally controlled thermostat which is in line of HACCP norms and provides visual alarm as a warning of the increasing or decreasing temperatures.
- Designed to work with both hot and cold inlet water.
- It is possible to transform one of the GNs to soup dispenser with the available accessory.
- Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.

Construction

- Heating elements connected to the well bottom include safety thermostat.
- Well bottom is inclined to facilitate water drainage.
- IPx4 water protection.
- Well in 304 AISI stainless steel with rounded corners to facilitate cleaning operations. The well is also equipped with a drain hole.
- Electronic control with temperature display.

Sustainability

- Etched foil heating elements to maximize heat transmission for reduced warm-up times.
- 19mm thick rock wool isolated with galvanize sheet guarantees excellent well insulation to reduce energy dispersion.

Recommended Detergents

PNC Code	Description
0S2881	S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T
0S2883	S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity
0S2884	S04 GLASSES & HARD SURFACES CLEANERS; 6 BOTTLES X 750ML
0S3257	S05 - MULTIPURPOSE DEGREASER; 6PCS X 750ML; ADR&IMDG Limited Quantity

Technical specifications

Electric

Supply voltage:	380-410 V/3N ph/50/60 Hz
Electrical power max.:	4.02 kW

Water:

Drain line size:	1"
Water inlet "CW" connection:	1/2"


Key Information:

External dimensions, Width:	1740 mm
External dimensions, Depth:	620 mm
External dimensions, Height:	260 mm
Net weight:	41.1 kg
Shipping weight:	72 kg
Shipping height:	380 mm
Shipping width:	660 mm
Shipping depth:	1780 mm
Shipping volume:	0.45 m ³
Set temperature:	+85 / +95 °C


Sustainability

Noise level:	0 dBA
--------------	-------


Side



Top



Other



D = Drain

EI = Electrical inlet (power)

ED = Remote electrical connection