

**535096 (NLPWDRE)**

Large pre-wash zone for Dual Rinse Rack Type Dishwasher

Main Features

- IP25 protection against water jets, solid objects and small animals (larger than 6 mm).
- Built-in drain valve in the tanks allows automatic dump and fill to refresh the water in the tank without any interruption of the washing process.
- Pre-wash section uses cold water so food remains are not "baked" onto the plates in order to have better pre-wash performance.
- Manual process of pre-wash spraying replaced by automatic prewash module before the main wash section.
- The feeding direction can be either left to right or right to left as it's reversible on site.
- Large counter balanced inspection door allows unrestricted all-round access to the internal area. Door is insulated with injected foam. This adds strength as well as reduces noise and heat loss.
- Automatic drain, clean and sanitize cycles featured as standard. The internal chamber, including the internal door is completely cleaned or sanitized avoiding bacteria proliferation for maximum hygiene and reducing manual work/time for operator.
- Deep drawn pressed tank with fully rounded corners, sloped towards the drain to prevent dirt build-up, provides fast drainage in just a few minutes. With no welding points the pressed tank offers a guaranteed water tight solution.
- The unit must be connected with dual rinse rack type dishwasher.

Construction

- Adjustable feet for full access underneath the machine for cleaning.
- All main components made in heavy duty anti-corrosive 304 type stainless steel: internal chamber, external, front and side panels, pre-wash arms and rack transportation system.
- The unit is built on modularity concept to easily connect with dual rinse rack type dishwasher without any modification including power, inlet water, drain water, detergent and rinse aid connections.



A focus on sustainability

Sustainability

- Auto-start/stop ensures that the zone runs only when a rack is passing through it. This reduces both water, energy consumption and noise.
- Multi-stage advanced filtering system removes soil from the pre-wash water providing cleaner water thus ensuring better washing performance.

Certifications & Recognitions



International system for mutual acceptance of test reports and certificates concerning the safety of electrical and electronic components, equipment, and products.




Product assessed by the manufacturer and deemed to meet EU safety, health, and environmental protection requirements.

Technical specifications


Electric	
Supply voltage:	380-415 V/3N ph/50 Hz
Pre-wash tank heating elements:	[[TechSpec].sPWTankHEP VALUE NOT FOUND] kW
Default Installed Power:	15.5 kW
Pre-wash pump size:	[[TechSpec].sSWWashPumpP VALUE NOT FOUND] kW
Water:	
Pre-wash tank size:	[[TechSpec].sSWTankCap VALUE NOT FOUND] l
Key Information:	
External dimensions, Width:	890 mm
External dimensions, Depth:	825 mm
External dimensions, Height:	1785 mm
Height with door open:	[[TechSpec].fHOpenDoor VALUE NOT FOUND] mm
Charging hole size (width):	[[TechSpec].fChargeHoleW VALUE NOT FOUND] mm
Charging hole size (height):	[[TechSpec].fChargeHoleH VALUE NOT FOUND] mm
Net weight:	157 kg
Shipping weight (gross):	157 kg
Shipping height:	2030 mm
Shipping width:	910 mm
Shipping depth:	1030 mm
Shipping volume:	1.9 m³
Pre-wash temperature:	[[TechSpec].fSWTempMin VALUE NOT FOUND] - [[TechSpec].fSWTempMax VALUE NOT FOUND] °C
Sustainability	
Noise level:	<62 dBA

Installation drawings


Front



Side



Top



D = Drain
HWI = Hot water inlet
EO = Electrical Outlet
U = USB port

EI = Electrical inlet (power)
EQ = Equipotential screw
CWI = Cold Water Inlet
ES = Electrical signal IN/OUT

Accessories

Optional Accessories

PNC Code	Description
Installation solutions	
865281	Kit to convert pre-wash module to wash module