

Handling System for Rack Type Loading Dishwashing Driven 90° Curve - Clockwise direction

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



865247 (HSLC90C)

Loading curve unit, 90°,
dishwasher driven, clockwise

Main Features

- Designed to transport 500x500 mm dishwashing baskets.
- "Key holes" and "snap on" system reduces the number of screws needed for fast and easy installation.
- The curve is driven by the dishwasher as the feeding arm in the curve will be connected with the conveyor of the dishwasher.
- Available clockwise direction for loading area.
- Loading curves provided with anti-jamming device to avoid rack jam.
- 45° cut corner to reduce space usage.
- Dishwasher curve 90° is intended for installation between a dishwasher and a roller conveyor or manual sorting table (on the loading side).

Construction



- Three legs included.
- Stainless steel feet 50 mm adjustable in height to align the operation height between the dishwasher and table.
- AISI 304 1,2mm stainless steel basin.
- 40x40mm stainless steel tubular and square legs.
- All surfaces smooth with polished finish.
- Sloping bottom of the table grants a smooth and rapid drainage.
- Thick welded flanges for sturdy connection between the units.

Optional Accessories


- Cover plate for 90° curve unit PNC 863237 ☐
- Emergency stop kit for Rack Type Dishwasher PNC 865162 ☐

APPROVAL: _____

Handling System for Rack Type Loading Dishwashing Driven 90° Curve - Clockwise direction

Front

Side


D = Drain

Top

Key Information:

External dimensions, Width:

865247 (HSLC90C) 850 mm

External dimensions, Depth: 850 mm

External dimensions, Height: 910 mm

Net weight: 25 kg

Height adjustment: 50/50 mm

Position to dishwasher: Loading

Basin material: Stainless Steel AISI 304 - EN 1.4301

Handling System for Rack Type
 Loading Dishwashing Driven 90° Curve - Clockwise direction

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.07.27