

**110881 (ZRI075R1G)**

1-glass door Roll-in Refrigerator 750lt, +2/+10°C, AISI 304, R290

Main Features

- Adjustable bottom door gasket.
- Automatic defrost and automatic evaporation of defrost water.
- Digital control panel with temperature display.
- Excellent space optimisation thanks to the compact dimensions (footprint 0.56m²).
- Interior light and lockable door.
- Lift-up control panel to better access main components.
- Simple cooling unit easily accessible from the rear of the appliance.
- Suitable for all kinds of 18 shelves GN 1/1 trolleys, designed to fit the 18 shelves GN 2/1 trolley available as optional accessory.
- The operating temperature can be adjusted from +2 to +10°C to suit both meat and dairy storage requirements.
- Ventilated cooling for optimal temperature distribution.
- Complies with main international certification bodies and is CE marked.
- Right hinged glass door.
- Inner side protectors to protect the internal walls.
- Tropicalized unit.

Construction

- Built-in compressor to suit operating conditions.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Evaporator and fan are placed outside the cell to provide the maximum storage capacity.
- Evaporator cover is easily removable for service.
- External panels are in AISI 304 stainless steel for higher level of hygiene.
- Interior cell and external panel are constructed in 304 AISI stainless steel.
- Lockable door.
- Electrical connection: 220-240V-single phase 50HZ or 220-240V-single phase 60HZ.

User Interface & Data Management

- Large digital white-digit display with humidity selection button (3 preset level), internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).
- Connect the product (with accessory) to the OneConnected Platform via Wi Fi or ethernet connection for a seamless remote experience. Real-time monitoring and analytics, alarm management, HACCP data management, APIs, and advanced features keep your fridge fully under control.

Sustainability

- Cabinet fitted with up to 60 mm thickness of Cyclopentane insulation for best insulating performance (thermal conductivity: 0,020 W/m*K). CFC and HCFC-free insulation.
- CFC and HCFC-free insulation.
- Finished in top quality materials to ensure durability.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.

Optional Accessories

PNC Code	Description
Feet, wheels and ramps	
881278	Insulated floor-ramp for 750lt Roll-in Refrigerator
Trolleys	
881521	Trolley 18 GN 2/1 for 750lt Roll-in

Recommended Detergents

PNC Code	Description
0S2881	S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T
0S2883	S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity
0S2884	S04 GLASSES & HARD SURFACES CLEANERS; 6 BOTTLES X 750ML
0S3257	S05 - MULTIPURPOSE DEGREASER; 6PCS X 750ML; ADR&IMDG Limited Quantity

Technical specifications

Electric

Supply voltage:	220-240 V/1 ph/50 Hz
Predisposed for:	220-230 V 60 Hz
Compressor power:	1/3 hp

Key Information:

External dimensions, Width:	750 mm
External dimensions, Depth:	816 mm
External dimensions, Height:	2101 mm
Number and type of doors:	1 Glass
External side panels:	Stainless Steel AISI 304
External top panels:	Galvanized Steel
External door material:	Glass
Internal panels material:	Stainless Steel AISI 304


Refrigeration Data

Operating temperature min.:	2 °C
Operating temperature max.:	10 °C


Sustainability

Refrigerant type:	R290
Refrigeration power:	520 W
Refrigerant weight:	145 g


Front



Side



Top



EI = Electrical inlet (power)

RO = Refrigerant Outlet

RI = Refrigerant Inlet

