

**110888 (ZRI093RE1FR)**

1-door Roll-in Refrigerator 930lt, 0+10°C, AISI 304, remote

Main Features

- Adjustable bottom door gasket.
- Automatic defrost and automatic evaporation of defrost water.
- Digital control panel with temperature display.
- Lift-up control panel to better access main components.
- Simple cooling unit easily accessible from the rear of the appliance.
- The operating temperature can be adjusted from 0 to +10 °C to suit both meat and dairy storage requirements.
- Ventilated cooling for optimal temperature distribution.
- Complies with main international certification bodies and is CE marked.
- One full door.
- Inner side protectors to protect the internal walls.
- Tropicalized unit.

Construction

- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Evaporator and fan are placed outside the cell to provide the maximum storage capacity.
- Evaporator cover is easily removable for service.
- External panels are in AISI 304 stainless steel for higher level of hygiene.
- Interior cell and external panel are constructed in 304 AISI stainless steel.
- Lockable door.
- Electrical connection: 220-240V-single phase 50HZ or 220-240V-single phase 60HZ.
- Remote compressor to suit operating conditions.

User Interface & Data Management

- Large digital white-digit display with humidity selection button (3 preset level), internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).
- Connect the product (with accessory) to the OneConnected Platform via Wi Fi or ethernet connection for a seamless remote experience. Real-time monitoring and analytics, alarm management, HACCP data management, APIs, and advanced features keep your fridge fully under control.

Sustainability

- Cabinet fitted with up to 60 mm thickness of Cyclopentane insulation for best insulating performance (thermal conductivity: 0,020 W/m*K). CFC and HCFC-free insulation.
- CFC and HCFC-free insulation.
- Finished in top quality materials to ensure durability.

Optional Accessories

PNC Code	Description
Feet, wheels and ramps	
881280	Insulated floor-ramp for 930lt Roll-in Refrigerator
Handling - bakery	
922761	Bakery/pastry trolley with rack holding 600x400mm grids for 20 GN 1/1 oven and blast chiller freezer, 80mm pitch (16 runners)
Handling - gastronorm	
922753	Trolley with tray rack, 20 GN 1/1, 63mm pitch
922754	Trolley with tray rack, 16 GN 1/1, 80mm pitch
Remote units	
880231	Remote unit for refrigerators and refrigerated counters, -2+10°C, R134a

Recommended Detergents

PNC Code	Description
0S2881	S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T
0S2883	S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity
0S2884	S04 GLASSES & HARD SURFACES CLEANERS; 6 BOTTLES X 750ML
0S3257	S05 - MULTIPURPOSE DEGREASER; 6PCS X 750ML; ADR&IMDG Limited Quantity

Technical specifications

Electric

Supply voltage: 220-240 V/1 ph/50/60 Hz

Key Information:

External dimensions, Width: 750 mm

External dimensions, Depth: 986 mm

External dimensions, Height: 2111 mm

Number and type of doors: 1 Full

External side panels: Stainless Steel AISI 304

External top panels: Galvanized Steel

External door material: Stainless Steel AISI 304

Internal panels material: Stainless Steel AISI 304

Refrigeration Data

Control type: Electronic

Operating temperature max.: 10 °C

Refrigeration type:

Suggested refrigeration power: 605 W

Condition at evaporation temperature: -10 °C


Condition at condensation temperature: 55 °C

Condition at ambient temperature: 32 °C


Connection pipes (remote) - outlet: 9.8 mm

Connection pipes (remote) - inlet: 6 mm

Front



Side



Top

