

**392272 (Z9GCGP8SGA)**

8-burner (2x10 kW, 6x6 kW) gas range on 2 gas ovens (8,5 kW each) - Australia

Construction

- Pan supports in stainless steel.

Included Accessories

PNC Code	Description	Quantity
164250	GN2/1 chrome grid for static oven	2

Optional Accessories

PNC Code	Description
Burner grids, plates, supports	
206170	Single burner radiant plate for pan support
206171	Single burner smooth plate for direct cooking - fits frontal burners only
206172	Single burner ribbed plate for direct cooking - fits frontal burners only
206298	Stainless steel grid for 2 burners
206363	Wok pan support for open burners (EVO700/900)
Chimney upstands	
206400	Chimney grid net, 400mm
Containers, trays and grids	
164250	GN2/1 chrome grid for static oven

PNC Code	Description
Feet, wheels and ramps	
206135	4 wheels, 2 swivelling with brake (EVO700/900). It is mandatory to install with base supports for feet/wheels.
206136	Flanged feet kit
206210	4 feet for concrete installation (not for 900 line freestanding grill)
206369	Base support for feet or wheels - 1600mm (EVO700/900)
206370	Base support for feet or wheels - 2000mm (EVO700/900)
Handrails	
206165	Side handrail for right/left hand
206192	Frontal handrail 1600 mm
216050	FRONTAL HANDRAIL 1600 MM
Installation solutions	
206086	Junction sealing kit
Kicking strips	
206152	Frontal kicking strip for concrete installation, 1600 mm
206157	Pair of side kicking strips for concrete installation
206179	Frontal kicking strip, 1600 mm
206180	Pair of side kicking strips
Other accessories	
927225	Pressure regulator for gas units
Panels	
206181	2 panels for service duct (single installation)
206202	2 panels for service duct (back to back installation)
Water taps	
206289	Water column with swivel arm (water column extension not included)
206290	Water column extension
Other accessories	
206335	2 side covering panels, height 700 mm, depth 900 mm
206385	Kit town gas nozzles (G150) for EVO900 gas ranges on gas oven

Technical specifications


Gas

Gas Power:	73 kW
Standard gas delivery:	Natural Gas G20 (20mbar)
Gas Type Option:	LPG; Natural Gas
Gas Inlet:	1/2"


Key Information:

Oven working Temperature:	120 °C MIN; 280 °C MAX
Oven Cavity Dimensions (width):	575 mm
Oven Cavity Dimensions (height):	300 mm
Oven Cavity Dimensions (depth):	700 mm
Net weight:	300 kg
Shipping weight (gross):	350 kg
Shipping height:	1030 mm
Shipping width:	1780 mm
Shipping depth:	1020 mm
Shipping volume:	1.87 m ³
Front Burners Power:	6 - 6 kW
Back Burners Power:	10 - 10 kW
Middle Burners Power:	6 - 6/6 - 6 kW
Certification group:	N9CG
Back Burners Dimension - mm	Ø 100 Ø 100
Front Burners Dimension - mm	Ø 60 Ø 60
Middle Burners Dimension - mm	Ø 60 Ø 60 Ø 60 Ø 60


Front



Side



Top



G = Gas connection



Part of



**Electrolux
Professional
Group**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

www.zanussiprofessional.com

2026/07/16

3/3