

**641398 (STCF3040)**

304 s/s island hood with filters and lamps

Main Features

- Low noise level.
- External panels with upturned edges to avoid injuries.
- Heating and air conditioning costs reduced thanks to the compensated air flow.

Construction

- Entirely constructed in 304 AISI stainless steel.
- Labyrinth filters guarantee constant filtration to avoid clogging and to protect against fire.
- Outlet holes are sized in order to minimize drops in pressure.
- 304 AISI stainless steel labyrinth filters easily removable for cleaning.
- Built-in lighting with protective screen.
- Optional accessory: air intake Plenum, which is insulated to avoid condensation.
- Rear exhaust with filters and front air intake through a narrow slot sized to obtain the correct induction effect.
- Perforated panel inside the intake circuit guarantees a perfect and uniform air distribution.
- Completely insulated intake area to avoid external condensation.
- Two separate air circuits (extraction and intake) to reduce the quantity of treated air released in the environment.
- Constructed as 2 separate wall units to join on site back to back.
- Central gutter with drain hole to transfer grease into two 304 AISI containers.

Optional Accessories

PNC Code	Description
----------	-------------

Other accessories

644801	LED strip for hoods 1250 mm
--------	-----------------------------

Technical specifications

Electric

Supply voltage: 220 V/1N ph/50 Hz

Key Information:

External dimensions, Width: 4000 mm

External dimensions, Depth: 3000 mm


External dimensions, Height: 500 mm

Net weight: 492 kg


Air Emission:

Air capacity: 15200 mc/h

Side



Top



EI = Electrical inlet (power)

